RESTO KITT

INDOOR REPAIR PUTTY (TO BE PAINTED OVER IF USED OUTDOORS)

- Quick-drying putties that can be mixed together and are easy to sand, ideal to repair damaged timber surfaces of furniture, stairs, windows, doors, etc.
- Environment-friendly and solvent-free. Soluble in water and alcohol



CODES AND DIMENSIONS

| CODE | colour | net weight | | pcs |
|-----------|---------------------|------------|-------|-----|
| | | [g] | [lbs] | |
| RESTOK15 | white | 200 | 0.44 | 1 |
| RESTOK13 | fir | 200 | 0.44 | 1 |
| RESTOK11 | pine | 200 | 0.44 | 1 |
| RESTOK23 | light beech | 200 | 0.44 | 1 |
| RESTOK08 | american cherry | 200 | 0.44 | 1 |
| RESTOK09 | antique light ash | 200 | 0.44 | 1 |
| RESTOK12 | light oak | 200 | 0.44 | 1 |
| RESTOK05 | light walnut | 200 | 0.44 | 1 |
| RESTOK22 | medium oak | 200 | 0.44 | 1 |
| RESTOK24 | medium beech | 200 | 0.44 | 1 |
| RESTOK03 | steam treated beech | 200 | 0.44 | 1 |
| RESTOK07 | cherry | 200 | 0.44 | 1 |
| RESTOK04 | walnut | 200 | 0.44 | 1 |
| RESTOK02 | light mahogany | 200 | 0.44 | 1 |
| RESTOK01 | mahogany | 200 | 0.44 | 1 |
| RESTOK13L | fir | 450 | 1.0 | 1 |





INDICATIONS FOR USE

The surface to be treated must be dry and free of dust and lubricants. If the cavity is too deep, a second layer may be required after sanding. After final sanding, the surface can be etched, oiled, waxed or painted.